

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 July 2004 (01.07.2004)

PCT

(10) International Publication Number
WO 2004/054765 A1

- (51) International Patent Classification⁷: **B27K 3/02**, (74) Agent: **BALDWIN SHELSTON WATERS**; PO Box 5999, Wellesley Street, 1000 Auckland (NZ).
- (21) International Application Number: **PCT/NZ2003/000277** (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 12 December 2003 (12.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (30) Priority Data: 523249 16 December 2002 (16.12.2002) NZ
- (71) Applicant (*for all designated States except US*): **MAT-TERSMITHS HOLDINGS LIMITED** [NZ/NZ]; 35 Renoir Street, West Harbour, Auckland (NZ).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **MAYNARD, Nigel, Paul** [NZ/NZ]; 35 Renoir Street, West Harbour, Auckland (NZ).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*



WO 2004/054765 A1

(54) Title: **METHOD OF DELIVERING COMPOSITIONS TO SUBSTRATES**

(57) Abstract: Method of delivering compositions to organic substrates, particularly lumber. Method involves heating a target zone of the substrate and then applying the composition to the surface of the substrate wherein the temperature of the composition is lower than that of the target zone of the substrate. Compositions include biocidal, strength modifiers, waterproofing and polymers.